

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 1 227 496 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
31.07.2002 Bulletin 2002/31

(51) Int Cl.7: **G11C 11/34**, **G11B 9/08**,  
**G11B 5/00**

(21) Application number: **01300399.1**

(22) Date of filing: **17.01.2001**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Smith, Charles**  
**Cambridge CB3 0HE (GB)**

(74) Representative: **Haley, Stephen**  
**Gill Jennings & Every,**  
**Broadgate House,**  
**7 Eldon Street**  
**London EC2M 7LH (GB)**

(71) Applicant: **CAVENDISH KINETICS LIMITED**  
**Nr Royston, Hertfordshire SG8 8PZ (GB)**

**(54) Non-volatile memory**

(57) The present invention seeks to provide a non-volatile memory device which has an increased density of storage elements formed thereon.

A non-volatile memory device comprises a substrate (2) supporting an array of field effect transistor devices. A plate is movable with respect to the substrate supporting an array of insulated charge storing elements (6) each having gate-forming metal plates (7) adjacent thereto. There is also means (12) for moving the plate with respect to the substrate such that, in use, the plate can be moved to position different charge storing elements over one of the array of field effect transistors so that each field effect transistor is able to determine the charge stored on more than one element. A corresponding magnetic effect device is also provided.

ments (6) each having gate-forming metal plates (7) adjacent thereto. There is also means (12) for moving the plate with respect to the substrate such that, in use, the plate can be moved to position different charge storing elements over one of the array of field effect transistors so that each field effect transistor is able to determine the charge stored on more than one element. A corresponding magnetic effect device is also provided.




Figure 3

2

EP 1 227 496 A1

Figure 4




Figure 5

## Description

[0001] This invention relates to a non-volatile memory.

[0002] Non-volatile memories are well known in the art. The preferred manner of operation of such devices is to provide a region which is insulated and on which charge can be stored. A semiconductor device is then placed adjacent to the insulated region to detect the amount of charge stored thereon. An individual element is such a device generally has a conducting plate, often called a gate formed on the insulating region surrounding the charge storing region, with a semiconductor field effect transistor placed on the side of the charge storing region opposite to the gate. The semiconductor field effect transistor is used to determine the amount of charge stored in the charge storage region. At a particular threshold voltage the semiconductor field effect transistor conducts current and the threshold voltage changes if charge is stored between the gate and the transistor. Charge is stored in the charge storage region by providing conducting islands or providing a layer of insulator with a small band cap.

[0003] Of course, known non-volatile memory devices have many arrays of individual elements, meaning that each element has to have placed around it column and row address electrodes for selection of particular elements within an array when reading of the element is required. Because of this, each individual element has a foot print which is comparatively large with respect to the region on which charge is stored. This large foot print is a severe restriction on the overall minimum size of a non-volatile memory device, as there is a minimum manufacturing size for each of the components of an individual element. This makes it difficult to increase the storage capacity of non-volatile memories without also increasing their overall physical dimensions.

[0004] The present invention seeks to provide a non-volatile memory device which has an increased density of storage elements formed thereon.

[0005] According to the present invention there is provided a non-volatile memory device comprising:

a substrate supporting an array of field effect transistor devices;

a plate movable with respect to the substrate supporting an array of insulated charge storing elements each having gate-forming metal plates adjacent thereto; and

means for moving the plate with respect to the substrate such that, in use, the plate can be moved to position different charge storing elements over one of the array of field effect transistors so that each field effect transistor is able to determine the charge stored on more than one element.

[0006] By providing a plate of charge storing elements that can be moved with respect to the field effect tran-

sistors, it is possible to pack the charge storing elements far more closely than in prior art devices. This increases the overall storage density of the device. The substrate may be appropriately doped silicon.

[0007] The plate may be attached to the substrate by anchor points and at least one flexible member associated with each anchor point. The flexible members may be formed from metal and may act as conducting connecting regions for the gates on the plate.

[0008] The means for moving the plate may comprise of one or more ribbed conducting elements attached to the plate in combination with one or more ribbed elements fixed to the substrate, such that a charge applied to one of the elements shifts it with respect to the other.

[0009] The field effect transistors may have sources which are shaped so as to enable them to be driven to charge individual charge storing elements.

[0010] According to the present invention there is also provided a non-volatile memory device comprising:

a substrate supporting an array of magnetic field detecting devices;

a plate movable with respect to the substrate supporting an array of elements formed from a magnetisable material, each having a magnetising device associated therewith; and

means for moving the plate with respect to the substrate such that, in use, the plate can be moved to position different magnetisable elements over one of the array of magnetic field detecting devices so that each magnetic field detecting device is able to determine the magnetisation of more than one magnetisable element.

[0011] With such a device the same benefits in terms of increased density of data storing elements are provided as with the first aspect of the invention. Furthermore, with the configuration of the present invention it is possible to build in redundancy so that manufacturing yields can be increased. In other words, if several read cells are not working due to errors in manufacture, then data can still be stored and read by using an adjacent read cell. Accordingly, with the invention, even if there were only a 50% yield in production of cells, the entire area of the device could still be used to store data.

[0012] The magnetic field detecting devices may be Hall effect devices or a magnetic multilayer, the resistance of which is very sensitive to magnetic fields. Again, the plate may be attached to the substrate by anchor points and at least one flexible member associated with each anchor point. In this case the flexible members may also be formed from metal and may act as conducting connecting regions for the magnetising devices on the plate.

[0013] One example of the present invention will now be described with reference to the accompanying drawings, in which:

Figure 1 is a schematic side view of a prior art non-volatile memory element;

Figure 2 is a schematic plan view of the element of figure 1;

Figure 3 is a schematic side view of a first example of the present invention;

Figure 4 is a plan view of a memory device having memory elements of the type shown in figure 3;

Figure 5 is a side schematic view of a device of figure 4;

Figure 6 is a plan view of active device area of the device of figures 4 and 5;

Figure 7 is a plan view of the footprint of the device of figures 4 and 5;

Figures 8A to 8C are schematic side views of further examples of elements according to the invention;

Figures 9 to 11 are schematic views showing manufacturing steps performed during construction of a device according to the invention; and

Figures 12A and 12B are schematic views of a magnetic storage device according to the invention.

[0014] Figure 1 shows a prior art memory element 1 of the type described above. As can be seen, a field effect device is formed on an appropriately doped silicon substrate 2 and is provided with a source 3 and a drain 4. Also formed on the surface of the substrate 2 are insulating layers 5 which surround a charge storing element 6. A gate 7 is formed from a conductor, such as a metal, on top of the insulators 5. Figure 2 shows a plan view of the element of figure 1, with reference numeral 8 denoting the footprint of a single element. As discussed above, the field effect transistor formed on the substrate 2 has a threshold voltage that is dependent upon the amount of charge stored in the element 6, and the threshold voltage can therefore be used to determine whether or not the amount of charge stored on the element 6 represents a 0 or a 1, and hence the bit of data stored on the element. As is also discussed above, the memory element 1 has a large footprint, mainly because of the size of the components of the field effect transistor.

[0015] Figure 3 shows a side schematic view of an example element employed in a device according to the invention. Components which correspond to those in figures 1 and 2 are numbered identically.

[0016] The underlying operation of the element is similar to that of the prior art device, although the charge storing element 6, together with its surrounding insulation 5 and gate 7 is formed on a plate 9 which is movable with respect to the substrate 2. The plate 9 is held above the substrate 2 such that there is a gap 10 that will generally be of a width of 1 micron or less. In use the basic operating principle of the element shown in figure 3 is that the plate 9 can be moved so that adjacent charge storing elements 6 on the plate 9 can, in turn, have the charge value stored thereon determined by the field effect device formed on the substrate 2.

[0017] Figure 4 is a plan view of a small device combining an array of elements of the type shown in figure 3. Again, components which correspond to those described above are numbered identically. As can be seen from this figure, and from figure 5, the movable plate 9 has a plate driving construction 12 which is formed from one or more comb actuators attached to the plate 9 and formed from a metal or other conductor. It also has fixed conducting comb actuators 12 that may be attached to the substrate 2. These actuators 12 can, in use, have an electrostatic charge applied thereto so that they move with respect to one another and thereby move the plate 9 with respect to the substrate 2.

[0018] As can be seen from figure 5, flexible members 13 support the plate 9 and form metal contacts for the gate-forming plates 7.

[0019] The flexible support members 13 are configured, by appropriate selection of the dimensions of width ( $w_g$ ), length ( $y$ ) and high ( $z$ ) to provide an appropriate spring force to enable accurate positioning control of the moveable plate 9 and to prevent vibration effects, but are flexible enough to allow rapid movement of the plate as required. These dimensions are shown in figure 11. The flexible members are also configured to enable the plate 9 to move in a vertical direction with respect to the plane of the substrate 2. This is to enable the movable plate 9 to be drawn into contact with the face of the field effect device that is formed on the substrate 2 so that charge can be applied to charge storing elements 6 as and when required, and so that accurate determination of charge levels can be made.

[0020] In use, the control of the position of the plate 9 is provided by position detecting field effect devices (not shown) formed on the substrate 2. These can provide appropriate feedback to the comb actuators 12 to provide accurate positioning. When the device is in operation it may be desirable, in order to have seamless writing and reading of individual charge storage elements, to provide the device of the invention with a dynamic random access memory (DRAM) which can buffer data either for input or output so that compensation can be made for delays in movement of the plate to provide appropriate reading.

[0021] To ensure a good packing density the sub cells have to be large enough so that the area of the chip lost to the actuation regions is small in comparison to the area of the sub cell containing the moving platform with the charged insulator and gate lines. Figure 7 shows a schematic diagram of the sub cell (area LW) and areas lost to actuation machinery (grey areas  $4x^2+2Wx+2Lx$ ). The sub cell has to be moved by at most F in either direction, F being the dimension of a read cell. To make sure that less than 10% of the chip is lost in this fashion we need  $(LW/(4x^2+2Wx+2Lx)) > 10$ . If we need the actuation device to be 10 times the movement then  $x=10F$  so  $(LW/(400F^2+20WF+21w)) > 10$ . If  $L=W$  then  $L^2-400LF-400F^2 > 0$  or for L much greater than F, L needs to be greater than 400F. For a read cell of side 0.4 mi-

crons this gives an area for the sub cell of  $(160\mu\text{m})^2$ .

[0022] There can be around ten thousand field effect devices under each moving plate of around  $(100\mu\text{m})^2$ . With a minimum feature size of  $0.2\mu\text{m}$  the device can store over 25 bits of information above each field effect transistor. That is 250 thousand bits of information. In a 1cm square chip the device could therefore store 2.5 Giga bits of information.

[0023] Figure 8A shows how a sharp feature 14 defined on the source side of the field effect device can be used to inject charge into a small region of the movable plate 9. The charge storing element 6 could be an  $\text{Si}_3\text{N}_4$  layer placed between two  $\text{SiO}_2$  layers. The charge would then remain localised in the region 6 of the plate 9 that is smaller than the minimum definable feature size. The charge elements 6 could be poly-silicon islands either within the  $\text{SiO}_2$  layer or join the bottom side of it on the bottom of the movable plate 9 or could be on small metal islands defined on the bottom of the movable plate 9. These are also below an insulator 5 with the gate 7 on top. A large electric field defined between the gate 7 and the source 3 is used to inject or remove electrons (or add holes). A negative voltage is applied, in use to a gate 7 whilst a positive voltage is applied to a source 3 via a line. This provides an electric field that is large enough to lead to tunnelling of electrons in the selected cell. The field at all other cells remains below activating threshold. To improve the resolution of the field effect device so that it could read the charge state of very small areas, the active area of the device should be made very small. This can be achieved by diffusing the n type dopants under the oxide. In this way the channel length can be made shorter than the minimum feature size. Using the metal of the source 3 and drain 4 to screen all but a small area of the charged plate would also help improve the spatial resolution of the field effect device (figure 8B). Figure 8C shows a further example of the invention in which a cantilever 20 is provided in conjunction with the source 3, a cantilever 20 also having a sharp feature 14, is provided. This can improve programming by the generation of a voltage difference between the cantilever 20 and the gate 7 so that the cantilever is drawn toward the plate 9 to ensure speedy and accurate charging. Once the voltage difference is removed the cantilever 20 moves back towards the base 2.

[0024] In a further adaptation of the invention, an additional transistor (not shown) may be provided on the substrate 2 for each individual cell that is formed on the substrate 2. The additional transistor is employed to specifically address an individual cell to reduce stray voltages that may disturb charges in other areas of the device. Whilst this would increase individual cell area, reliability and yield are improved and the number of gate line 7 can be reduced by having a single gate over all the storage elements 6.

[0025] Figure 9 and 10 show how the gates 7 could be made into support members for the plate 9 using a

sacrificial layer 15 put down before the gate layers 7. Sputter deposition of the gate metal 7 means that it conformally coats the sacrificial layer 15. This is then removed leaving an arch-like spring 13. The spring constant can be engineered so that the plate can be moved up and down perpendicular to the plane of the substrate, but have enough restoring force to overcome adhesion. The spring constant would also be such that the restoring force in the plane of the plate is not so large as to require large actuators to move them. Metal electrodes under the moving plate are used to pull the plate down onto bumps (not shown) near the field effect devices. The bumps reduce adhesion. With weak springs constants in the plane of the substrate 2, the position of the plate 9 can be controlled electrostatically using the actuators 12 and position detectors (not shown).

[0026] Figure 12A is a schematic plan view of a magnetic storage device that operates under the same principles as the device described above. In this example read lines 30 are placed above sensor lines 31. Figure 12B is a schematic diagram showing how individual elements can be magnetised by pulsing the current, via a transistor 32, 33, that passes through an individual sensor line 31 whilst a moving read line 30 is placed above it. For clarity the write line that would correspond to the gate 7 of the earlier example is not shown in figure 12B.

## Claims

### 1. A non-volatile memory device comprising:

a substrate supporting an array of field effect transistor devices;  
a plate movable with respect to the substrate supporting an array of insulated charge storing elements each having gate-forming metal plates adjacent thereto; and  
means for moving the plate with respect to the substrate such that, in use, the plate can be moved to position different charge storing elements over one of the array of field effect transistors so that each field effect transistor is able to determine the charge stored on more than one element.

2. A device according to claim 1, wherein the plate attached to the substrate by anchor points and the devices further comprises at least one flexible member associated with each anchor point.

3. A device according to claim 2, wherein the flexible members are formed from metal and act as conducting connecting regions for the gates on the plate.

4. A device according to any preceding claim, wherein the field effect transistors have sources which are

shaped so as to enable them to be driven to charge individual charge storing elements.

5. A device according to claim 4, wherein the sources have a cantilever associated wherewith, the cantilever being driven, in use, towards the moveable plate in order to transfer charge to a selected storage element. 5
  
6. A device according to any preceding claim, wherein each of the fields affects transistor devices has a further transistor associated therewith for selective addressing thereof in use. 10
  
7. A non-volatile memory device comprising: 15
  - a substrate supporting an array of magnetic field detecting devices;
  - a plate movable with respect to the substrate supporting an array of elements formed from a magnetisable material, each having a magnetising device associated therewith; and 20
  - means for moving the plate with respect to the substrate such that, in use, the plate can be moved to position different magnetisable elements over one of the array of magnetic field detecting devices so that each magnetic field detecting device is able to determine the magnetisation of more than one magnetisable element. 2530
  
8. A device according to claim 7, wherein the magnetic field detecting devices are Hall effect devices.
  
9. A device according to claim 7 or claim 8, wherein the plate may be attached to the substrate by anchor points and at least one flexible member associated with each anchor point. 35
  
10. A device according to claim 9, wherein the flexible members are formed from metal and act as conducting connecting regions for the magnetising devices on the plate. 40
  
11. A device according to any preceding claim, wherein the means for moving the plate comprises one or more ribbed conducting elements attached to the plate in combination with one or more ribbed elements fixed to the substrate, such that a charge applied to one of the elements shifts it with respect to the other. 45
  
12. A device according to any of the preceding claims manufactured by employing semiconductor manufacturing techniques. 50
  
- 55




Figure 1




Figure 2




Figure 3

Figure 4




Figure 5







Figure 6

Figure 7






Figure 8A




Figure 8B







Figure 8 c






Figure 12 a




Figure 12 b



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 01 30 0399

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	US 3 989 953 A (FISCHER DIETER) 2 November 1976 (1976-11-02) * the whole document *	1,12	G11C11/34 G11B9/08 G11B5/00
Y	US 5 065 102 A (NAKAGAKI SHINTARO ET AL) 12 November 1991 (1991-11-12) * column 16, line 32 - column 17, line 14; figures 26-28 *	1,12	
A	DE 38 23 010 A (LEITZ WILD GMBH) 21 September 1989 (1989-09-21) * the whole document *	1,12	
A	US 5 592 001 A (ASANO MASAMICHI) 7 January 1997 (1997-01-07) * abstract *	1,12	
A	US 5 751 683 A (KLEY VICTOR B) 12 May 1998 (1998-05-12) * the whole document * * column 16, line 63 - column 17, line 7 * * column 19, line 16 - column 20, line 27 * * column 21, line 18 - line 61 *	1,2,11, 12	TECHNICAL FIELDS SEARCHED (Int.Cl.7)  G11C G11B
A	US 5 593 306 A (KOHNE OLE B) 14 January 1997 (1997-01-14) * the whole document *	1-3,11, 12	
A	GB 2 060 980 A (TOKYO SHIBAURA ELECTRIC CO) 7 May 1981 (1981-05-07)		
A	EP 0 984 444 A (CANON KK) 8 March 2000 (2000-03-08)		
A	WO 98 44498 A (RENNER CHRISTOPHE ;AHN CHARLES H (CH); TYBELL THOMAS (CH); UNIV GE) 8 October 1998 (1998-10-08)		
-/--			
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>6 July 2001</b>	Examiner <b>FUX, J</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document I : theory or principle underlying the invention L : earlier patent document, but published on, or after the filing date D : document cited in the application C : document cited for other reasons F : member of the same patent family corresponding document			

EPC FORM 1 (03.03.92) (P34001)



European Patent  
Office

Application Number  
EP 01 30 0399

### CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

### LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☐ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☒ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:

1 - 3 , 11 , 12



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 30 0399

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 5 412 641 A (KAWASE TOSHIMITSU ET AL) 2 May 1995 (1995-05-02) * the whole document *		
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
<p><del>The present search report has been drawn up for all claims</del></p>			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>6 July 2001</b>	Examiner <b>FUX, J</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone  Y : particularly relevant if combined with another document of the same category  A : technological background  O : non-written disclosure  P : intermediate document</p> <p>T : theory or principle underlying the invention  E : earlier patent document, but published on, or after the filing date  D : document cited in the application  L : document cited for other reasons  &amp; : member of the same patent family, co-responding document</p>			

EP 01 30 0399 (1995-05-02)





European Patent  
Office

LACK OF UNITY OF INVENTION  
SHEET B

Application Number

EP 01 30 0399

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-3,11,12

A non-volatile charge-storage memory comprising a substrate supporting an array of field effect transistor devices; a plate supporting an array of insulated charge storage elements, the plate being attached to the substrate by at least one flexible member and the plate being movable with respect to the substrate to respectively position different charge storing elements over respectively one of the field effect transistor devices to respectively enable each of the field effect transistors to determine respectively the charge stored on more than one element.

2. Claims: 4,5

A non-volatile charge-storage memory comprising a substrate supporting an array of field effect transistor devices; a plate supporting an array of insulated charge storage elements, the sources of the field effect transistors being shaped or disposed so as to enable them to be driven to charge individual charge storage elements.

3. Claim : 6

A non-volatile charge-storage memory comprising a substrate supporting an array of field effect transistor devices; a plate supporting an array of insulated charge storage elements wherein each of the field effect transistor devices has a further transistor associated therewith for selective addressing thereof.

4. Claims: 7-10

A non-volatile memory comprising a substrate comprising an array of magnetic field detecting devices, a plate movable with respect to the substrate supporting an array of magnetisable storage elements, each having a magnetising device associated therewith, the plate being attached to the substrate by at least one flexible member and means for moving the plate with respect to the substrate such that in use the plate can be moved to position different magnetisable elements over one of the array of magnetic field detecting devices so that each detecting device is able to determine the magnetisation of more than one storage element.

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 0399

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-07-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3989953 A	02-11-1976	DE 2440907 B	02-01-1976
		FR 2299698 A	27-08-1976
		GB 1469919 A	06-04-1977
		JP 1161186 C	10-08-1983
		JP 51049643 A	30-04-1976
		JP 57056160 B	27-11-1982
		NL 7510052 A	02-03-1976
US 5065102 A	12-11-1991	JP 1284769 A	16-11-1989
		JP 1299472 A	04-12-1989
		JP 1865375 C	26-08-1994
		JP 5079945 B	05-11-1993
		JP 2035639 A	06-02-1990
		BR 8902529 A	01-03-1990
		CA 1326880 A	08-02-1994
		CN 1037769 A,B	06-12-1989
		DE 68919525 D	12-01-1995
		DE 68919525 T	04-05-1995
		EP 0341669 A	15-11-1989
		KR 9209911 B	06-11-1992
		US 5260796 A	09-11-1993
		US 5268763 A	07-12-1993
DE 3823010 A	21-09-1989	NONE	
US 5592001 A	07-01-1997	JP 2685966 B	08-12-1997
		JP 4057293 A	25-02-1992
		DE 69130993 D	22-04-1999
		DE 69130993 T	29-07-1999
		EP 0463580 A	02-01-1992
		KR 9510725 B	22-09-1995
US 5751683 A	12-05-1998	AU 6637696 A	18-02-1997
		WO 9704449 A	06-02-1997
		US 2001010668 A	02-08-2001
US 5593306 A	14-01-1997	DK 120994 A	20-04-1996
		AU 3427695 A	02-05-1996
		EP 0708428 A	24-04-1996
		JP 8227268 A	03-09-1996
GB 2060980 A	07-05-1981	JP 55139643 A	31-10-1980
		JP 55139644 A	31-10-1980
		DE 3041414 C	21-07-1983
		DE 3041414 T	11-02-1982
		WO 8002342 A	30-10-1980

EPO FORM P449

For more details about this annex : see Official Journal of the European Patent Office No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 0399

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-07-2001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0984444	A	08-03-2000	JP 2000067478 A	03-03-2000
			JP 2000268421 A	29-09-2000
WO 9844498	A	08-10-1998	FR 2761530 A	02-10-1998
			EP 0972284 A	19-01-2000
US 5412641	A	02-05-1995	JP 3029499 B	04-04-2000
			JP 5314549 A	26-11-1993

EPO FORM PC-455

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82